

TYPICAL PARABOLIC LAYOUT

Base Line (Edge of paved shoulder or offset line of edge of traveled way)

Begin flare

$Y = \frac{WX^2}{L^2}$

Y = Offset from base line  
W = Maximum offset  
X = Distance along base line  
L = Length of flare



DIST	COUNTY	ROUTE	KILOMETER TOTAL	POST PROJECT	SHEET NO.	TOTAL SHEET

*Ellis K. Hirst*

REGISTERED CIVIL ENGINEER

**July 1, 2004**  
PLANS APPROVAL DATE

The State of California or its officers or agents, shall not be responsible for the accuracy or completeness of electronic copies of this plan sheet.

**ELLIS K. HIRST**  
No. **C17926**  
Exp. **6-30-05**  
CIVIL  
STATE OF CALIFORNIA

To get the Caltrans web site, go to: <http://www.dot.ca.gov>

## NOTES

- |   |  |
|---|--|
| <p>1. Line post, blocks and hardware to be used are shown on Standard Plans A77A1, A77A2, A77B1, A77C1 and A77C2.</p> <p>2. Guard rail post spacing to be 1905 mm center to center, except as otherwise noted.</p> <p>3. Except as noted, line posts are 150 mm x 200 mm x 1.83 m wood with 150 mm x 200 mm x 360 mm wood blocks. MW 150 x 14 steel posts, 1.83 m in length, with 150 mm x 200 mm x 360 mm notched wood blocks or plastic blocks may be used for 150 mm x 200 mm x 1.83 m wood post with 150 mm x 200 mm x 360 mm wood blocks where applicable and when specified.</p> <p>4. Direction of adjacent traffic indicated by ➡.</p> <p>5. Layout Types 11D through 11L, shown on the A77E Series of Standard Plans, are typically used where guard railing is recommended to shield embankment slopes and a crashworthy end treatment is required for both directions of traffic. See Railing Case 6 in Diagram No. 5 on Standard Plan A77D1.</p> <p>6. In-line Terminal System End Treatments are used where site conditions will not accommodate a flared end treatment.</p> | <p>7. The type of terminal system end treatment to be used will be shown on the Project Plans.</p> <p>8. Dependent on site conditions (embankment height and side slope), construction of additional guard railing (length equal to multiples of 3.8 m with 1.9 m post spacing) may be advisable.</p> <p>9. Where placement of dike is required with guard railing installations, see Standard Plan A77C4 for dike positioning details.</p> <p>10. The 15:1 or flatter flare used with buried end anchors is based on the edge of the paved shoulder or offset line of edge of the traveled way. The length of guard railing within the 15:1 or flatter flare is based on site conditions and should be a length equal to multiples of 3.8 meters.</p> <p>11. For details of the buried post end anchor used with Type 11I Layout, see Standard Plan A77I2.</p> <p>12. For typical flare offsets for 7.6 m length parabola with maximum offset of 305 mm, see Standard Plan A77E1.</p> |
|---|--|

## METAL BEAM GUARD RAILING TYPICAL LAYOUTS FOR EMBANKMENTS

NO SCALE

ALL DIMENSIONS ARE IN  
MILLIMETERS UNLESS OTHERWISE SHOWN

A77E5